

Control structures

Control structures direct the flow of a program using logical statements. For example, conditionals (**if-elif-else**) allow a program to skip sections of code, and iteration (**while**), allows a program to repeat a section.

Conditional statements

Conditional statements let programs execute different lines of code depending on certain conditions. Let's review the **if-elif-else** syntax:

- The **elif** and **else** clauses are optional, and you can have any number of **elif** clauses.
- A **conditional expression** is an expression that evaluates to either a truthy value (**True**, a non-zero integer, etc.) or a falsy value (**False**, 0, **None**, "", [], etc.).
- Only the first **if/elif** expression that evaluates to a **truthy** value will have its corresponding indented suite be executed.
- If none of the conditional expressions evaluate to a true value, then the **else** suite is executed. There can only be one **else** clause in a conditional statement.

Here's the general form:

```
if <conditional expression>:  
    <suite of statements>  
elif <conditional expression>:  
    <suite of statements>  
else:  
    <suite of statements>
```

Boolean Operators

Python also includes the **boolean operators** **and**, **or**, and **not**. These operators are used to combine and manipulate boolean values.

- **not** returns the opposite boolean value of the following expression, and will always return either **True** or **False**.
- **and** evaluates expressions in order and stops evaluating (short-circuits) once it reaches the first falsy value, and then returns it. If all values evaluate to a truthy value, the last value is returned.
- **or** evaluates expressions in order and short-circuits at the first truthy value and returns it. If all values evaluate to a falsy value, the last value is returned.

2 Control, Environment Diagrams

For example:

```
>>> not None
True
>>> not True
False
>>> -1 and 0 and 1
0
>>> False or 9999 or 1/0
9999
```

Q1: Case Conundrum

In this question, we will explore the difference between `if` and `elif`.

What is the result of evaluating the following code?

```
def special_case():
    x = 10
    if x > 0:
        x += 2
    elif x < 13:
        x += 3
    elif x % 2 == 1:
        x += 4
    return x

special_case()
```

What is the result of evaluating this piece of code?

```
def just_in_case():
    x = 10
    if x > 0:
        x += 2
    if x < 13:
        x += 3
    if x % 2 == 1:
        x += 4
    return x

just_in_case()
```

How about this piece of code?

```
def case_in_point():  
    x = 10  
    if x > 0:  
        return x + 2  
    if x < 13:  
        return x + 3  
    if x % 2 == 1:  
        return x + 4  
    return x  
  
case_in_point()
```

Which of these code snippets result in the same output, and why? Based on your findings, when do you think using a series of `if` statements has the same effect as using both `if` and `elif` cases?

Q2: Jacket Weather?

Alfonso will only wear a jacket outside if it is below 60 degrees or it is raining.

Write a function that takes in the current temperature and a boolean value telling if it is raining. This function should return `True` if Alfonso will wear a jacket and `False` otherwise.

Try solving this problem using an `if` statement.

Note: Since we'll either return `True` or `False` based on a single condition, whose truthiness value will also be either `True` or `False`. Knowing this, try to write this function using a single line.

```
def wears_jacket_with_if(temp, raining):  
    """  
    >>> wears_jacket_with_if(90, False)  
    False  
    >>> wears_jacket_with_if(40, False)  
    True  
    >>> wears_jacket_with_if(100, True)  
    True  
    """  
    "*** YOUR CODE HERE ***"  
  
# You can use more space on the back if you want
```

Q3: If Function vs Statement

Now that we've learned about how `if` statements work, let's see if we can write a function that behaves the same as an `if` statement.

```

def if_function(condition, true_result, false_result):
    """Return true_result if condition is a true value, and
    false_result otherwise.

    >>> if_function(True, 2, 3)
    2
    >>> if_function(False, 2, 3)
    3
    >>> if_function(3==2, 'equal', 'not equal')
    'not equal'
    >>> if_function(3>2, 'bigger', 'smaller')
    'bigger'
    """
    if condition:
        return true_result
    else:
        return false_result

```

Despite the doctests above, this function actually does *not* always do the same thing as an `if` statement.

We want to find a case where this `if_function` will behave differently from an `if` statement. To do so, implement the following functions,

- `cond`: Calling `cond` should act as the `if` condition.
- `true_func`: Calling `true_func` should represent the result of the truthy case.
- `false_func`: Calling `false_func` should represent the result of the falsey case.

so that `with_if_function` does *not* behave the same as `with_if_statement`, written in the doctests and here below:

- When `with_if_statement` is called, we print out 61A.
- When `with_if_function` is called, we print out both `Welcome to` and `61A` on separate lines.

Implement `cond`, `true_func`, and `false_func` below.

Hint: If you are having a hard time identifying how `with_if_statement` and `with_if_function` would differ in behavior, consider the [rules of evaluation for `if` statements](#) and [call expressions](#).

```

def if_function(condition, true_result, false_result):
    """Return true_result if condition is a true value, and
    false_result otherwise.

    >>> if_function(True, 2, 3)
    2
    >>> if_function(False, 2, 3)
    3
    >>> if_function(3==2, 'equal', 'not equal')
    'not equal'
    >>> if_function(3>2, 'bigger', 'smaller')
    'bigger'
    """
    if condition:
        return true_result
    else:
        return false_result

def with_if_statement():
    """
    >>> result = with_if_statement()
    61A
    >>> print(result)
    None
    """
    if cond():
        return true_func()
    else:
        return false_func()

def with_if_function():
    """
    >>> result = with_if_function()
    Welcome to
    61A
    >>> print(result)
    None
    """
    return if_function(cond(), true_func(), false_func())

def cond():
    """*** YOUR CODE HERE ***"""

def true_func():
    """*** YOUR CODE HERE ***"""

```

Note: This worksheet is a problem bank—most of this will not cover all the problems in discussion section.

While loops

To repeat the same statements multiple times in a program, we can use iteration. In Python, one way we can do this is with a **while loop**.

```
while <conditional clause>:  
    <statements body>
```

As long as <conditional clause> evaluates to a true value, <statements body> will continue to be executed. The conditional clause gets evaluated each time the body finishes executing.

Q4: Square So Slow

What is the result of evaluating the following code?

```
def square(x):
    print("here!")
    return x * x

def so_slow(num):
    x = num
    while x > 0:
        x = x + 1
    return x / 0

square(so_slow(5))
```

Hint: What happens to `x` over time?

Q5: Is Prime?

Write a function that returns `True` if a positive integer `n` is a prime number and `False` otherwise.

A prime number `n` is a number that is not divisible by any numbers other than 1 and `n` itself. For example, 13 is prime, since it is only divisible by 1 and 13, but 14 is not, since it is divisible by 1, 2, 7, and 14.

Hint: Use the `%` operator: `x % y` returns the remainder of `x` when divided by `y`.


```
def is_prime(n):  
    """  
    >>> is_prime(10)  
    False  
    >>> is_prime(7)  
    True  
    """  
    "*** YOUR CODE HERE ***"
```

```
# You can use more space on the back if you want
```

Q6: Fizzbuzz

Implement the fizzbuzz sequence, which prints out a *single statement* for each number from 1 to n . For a number i ,

- If i is divisible by 3 only, then we print “fizz”.
- If i is divisible by 5 only, then we print “buzz”.
- If i is divisible by both 3 and 5, then we print “fizzbuzz”.
- Otherwise, we print the number i by itself.

Implement `fizzbuzz(n)` here:

```
def fizzbuzz(n):  
    """  
    >>> result = fizzbuzz(16)  
    1  
    2  
    fizz  
    4  
    buzz  
    fizz  
    7  
    8  
    fizz  
    buzz  
    11  
    fizz  
    13  
    14  
    fizzbuzz  
    16  
    >>> result is None # No return value  
    True  
    """  
    "*** YOUR CODE HERE ***"
```

```
# You can use more space on the back if you want
```

Environment Diagrams

An **environment diagram** is a model we use to keep track of all the variables that have been defined and the values they are bound to. We will be using this tool throughout the course to understand complex programs involving several different assignments and function calls.

One key idea in environment diagrams is the **frame**. A frame helps us keep track of what variables have been defined in the current execution environment, and what values they hold. The frame we start off with when executing a program from scratch is what we call the **Global frame**. Later, we'll get into how new frames are created and how they may depend on their parent frame.

Here's a short program and its corresponding diagram:

See the web version of this resource for the environment diagram.

Remember that programs are mainly just a set of statements or instructions—so drawing diagrams that represent these programs also involves following sets of instructions! Let's dive in...

Assignment Statements

Assignment statements, such as `x = 3`, define variables in programs. To execute one in an environment diagram, record the variable name and the value:

1. Evaluate the expression on the right side of the = sign.
2. Write the variable name and the expression's value in the current frame.

Q7: Assignment Diagram

Use these rules to draw an environment diagram for the assignment statements below:

```
x = 11 % 4
y = x
x **= 2
```

def Statements

A **def** statement creates (“defines”) a function object and binds it to a name. To diagram **def** statements, record the function name and bind the function object to the name. It's also important to write the **parent frame** of the function, which is where the function is defined.

A very important note: Assignments for **def** statements use pointers to functions, which can have different behavior than primitive assignments (such as variables bound to numbers).

1. Draw the function object to the right-hand-side of the frames, denoting the intrinsic name of the function, its parameters, and the parent frame (e.g. `func square(x) [parent = Global]`).
2. Write the function name in the current frame and draw an arrow from the name to the function object.

Q8: def Diagram

Use these rules for defining functions and the rules for assignment statements to draw a diagram for the code below.

```
def double(x):  
    return x * 2  
  
def triple(x):  
    return x * 3  
  
hat = double  
double = triple
```